



BAOLAI STEEL



Screw Thread
螺纹管 A011/A012
60x3.0x195/220mm



Screw Rolled Thread
挤压螺纹管 A013/A014
60x3.0x210/300mm



Screw Thread
螺纹管 A015
76x3.5x235mm



Prop Sleeve
杯式螺母 A021
70X3.5X135mm



Adjustable Nut
调节螺母 A022
0.45kg



Adjustable Nut
调节螺母 A023
0.45kg



Adjustable Nut
调节螺母 A024/A025
0.75kg/1.13kg



Adjustable Nut
调节螺母 A026
0.80kg



Flower type Plate
冲压花盘 A031
120x120x4.0mm



Flat Square Plate
冲压方盘 A032
120x120x4.0mm



Butterfly type Plate
冲压蝶式盘 A033
120x120x4.0mm



Square type Plate
冲压方盘 A034
120x120x4.0mm



Fixed Pin D12
直销 A041 0.10kg



Chain Pin D12
链销 A042 0.12kg



G-pin hook D12/D14
弯销 A043/A044
0.32kg/0.43kg



Cap pin D12
盖销 A045 0.13kg

 <p>TH101</p>	 <p>TH112</p>	 <p>TH145</p>	 <p>TH156</p>																																						
	 <p>TH123</p>	 <p>TH134</p>																																							
	<p>Technical Specifications</p> <p>Maximum length: 4500mm Minimum length: 2500mm Surface finish: Pre-galvanized Pipe thickness: 2.5mm Outer tube: 60mm Inner tube: 48mm Strengthen tube: 70.5mm</p>																																								
	<table border="1"> <thead> <tr> <th>型号Model</th> <th>Min-Max Length</th> <th>Outer tube</th> <th>Inner tube</th> </tr> </thead> <tbody> <tr><td></td><td>600-1000mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>900-1500mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>1200-2000mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>1800-3200mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>2000-3500mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>2200-3900mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>2500-4500mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>3000-5000mm</td><td>60mm</td><td>48mm</td></tr> <tr><td></td><td>3500-5500mm</td><td>60mm</td><td>48mm</td></tr> </tbody> </table>			型号Model	Min-Max Length	Outer tube	Inner tube		600-1000mm	60mm	48mm		900-1500mm	60mm	48mm		1200-2000mm	60mm	48mm		1800-3200mm	60mm	48mm		2000-3500mm	60mm	48mm		2200-3900mm	60mm	48mm		2500-4500mm	60mm	48mm		3000-5000mm	60mm	48mm		3500-5500mm
型号Model	Min-Max Length	Outer tube	Inner tube																																						
	600-1000mm	60mm	48mm																																						
	900-1500mm	60mm	48mm																																						
	1200-2000mm	60mm	48mm																																						
	1800-3200mm	60mm	48mm																																						
	2000-3500mm	60mm	48mm																																						
	2200-3900mm	60mm	48mm																																						
	2500-4500mm	60mm	48mm																																						
	3000-5000mm	60mm	48mm																																						
	3500-5500mm	60mm	48mm																																						

 <p>TH210</p>	 <p>TH211</p>	 <p>TH232</p>	 <p>TH243</p>
	 <p>TH221</p>		
	<p>Technical Specifications</p> <p>Maximum length: 3900mm Minimum length: 2200mm Color: Orange painted Pipe thickness: 2.0mm Outer tube: 60mm Inner tube: 48mm Height adjustment: 125mm</p>		
<p>Jack post 3'-5'</p> <p>TH221</p>			

60/48 cup type



TH301

56/48 cup type



TH313

TH312

56/48 u type



TH323

型号Model

Min-Max Length	Outer tube	Inner tube
600-1000mm	56mm	48mm
900-1500mm	56mm	48mm
1200-2000mm	56mm	48mm
1800-3100mm	56mm	48mm
2000-3500mm	56mm	48mm
2200-3900mm	56mm	48mm
2500-4500mm	56mm	48mm
3000-5000mm	56mm	48mm
3500-5500mm	56mm	48mm

Technical Specifications

Surface Finish: Painted
 Color: Orange
 Safety Pin: Φ12mm
 Sleeve's handled: 12mm
 Sleeve's Length: 135mm
 Height adjustment: 100mm
 Ring of protection



48/40 cup type



TH401

48/40 cup type



TH412

48/40 type



TH423



A031



A032



A033

型号Model

Min-Max Length	Outer tube	Inner tube
900-1500mm	48mm	40mm
1200-2000mm	48mm	40mm
1800-3100mm	48mm	40mm
2000-3500mm	48mm	40mm
2200-3900mm	48mm	40mm
2500-4500mm	48mm	40mm



A020



A021



A030

Technical Specifications

Maximum length: 3500mm
 Minimum length: 2000mm
 Color: Orange
 Pipe thickness: 2.0mm
 Outer tube: 48mm
 Inner tube: 40mm
 Height adjustment: 125mm

60/48 U type



U型钢支柱 U type plate
110x90x30x4.0mm
120x90x35x5.0mm
120x90x50x5.0mm
160x120x50x5.0mm
220x150x90x6.0mm

TH501

60/48 T type



TH512
T plate: 540x55x15x2.0mm

型号 Model	Min-Max Length	Outer tube	Inner tube
	600-1000mm	60mm	48mm
	900-1500mm	60mm	48mm
	1200-2000mm	60mm	48mm
	1800-3100mm	60mm	48mm
	2000-3500mm	60mm	48mm
	2200-3900mm	60mm	48mm
	2500-4500mm	60mm	48mm
	3000-5000mm	60mm	48mm
	3500-5500mm	60mm	48mm

56/48 T type



TH523
T type plate: 540x55x15x2.0mm

60/48 L type



TH534
L type plate: 120x120x40x5.0mm

60/48 type



A014
TH601

56/48 type



A065
TH612

型号 Model	Min-Max Length	Outer tube	Inner tube
	900-1500mm	56/60mm	48mm
	1200-2000mm	56/60mm	48mm
	1800-3100mm	56/60mm	48mm
	2000-3500mm	56/60mm	48mm

48 type



TH623

型号 Model	Min-Max Length	Outer tube
	1000-1300mm	48mm
	2000-2300mm	48mm
	2500-2800mm	48mm
	3000-3300mm	48mm
	3500-3800mm	48mm
	4000-4300mm	48mm



A066



A067



A068



A069



A070



Adjustable Steel Prop (heavy duty prop middle east prop) 中东和德式支撑



最小高度 Min Height	最大高度 Max Height	内管直径 Inner tube	外管直径 Outer tube	壁厚 Tube Thk
1.6m	2.9m	48mm	60mm	1.4-4.0mm
1.8m	3.2m	48mm	60mm	1.4-4.0mm
2.0m	3.5m	48mm	60mm	1.4-4.0mm
2.0m	3.6m	48mm	60mm	1.4-4.0mm
2.2m	4.0m	48mm	60mm	1.4-4.0mm
3.0m	5.0m	48mm	60mm	1.4-4.0mm
3.5m	6.0m	48mm	60mm	1.4-4.0mm

Adjustable Shoring Prop

可调式钢支撑

Adjustable Steel Prop (Light duty prop-spanish prop) 西班牙式支撑



最小高度 Min Height	最大高度 Max Height	内管直径 Inner tube	外管直径 Outer tube	壁厚 Tube Thk
0.6m	1.1m	40mm	48mm	1.4-2.5mm
0.8m	1.4m	40mm	48mm	1.4-2.5mm
1.6m	2.9m	40mm	48mm	1.4-2.5mm
1.8m	3.2m	40mm	48mm	1.4-2.5mm
2.0m	3.6m	40mm <td 48mm	1.4-2.5mm	
2.2m	4.0m	40mm	48mm	1.4-2.5mm

Adjustable Steel Prop (Light duty prop-Italian prop) 意大利式支撑

最小高度 Min Height	最大高度 Max Height	内管直径 Inner tube	外管直径 Outer tube	壁厚 Tube Thk
1.6m	2.9m	48mm	56mm	1.4-2.5mm
1.8m	3.2m	48mm	56mm	1.4-2.5mm
2.0m	3.5m	48mm	56mm	1.4-2.5mm
2.0m	3.6m	48mm	56mm	1.4-2.5mm
2.2m	4.0m	48mm	56mm	1.4-2.5mm



Push-pull Brace (Can be customized accordingly) 斜拉式支撑



Tripod (Can be customized accordingly) 三脚架

6.8kg	7.45kg	8.4kg
-------	--------	-------

